



# Intellian “Enterprise” OW terminal

*Enterprise Flat Panel for Land Mobility*

The OW11FV is the ideal Flat Panel user terminal for Government and Transportation markets, delivering low-latency, high-speed connectivity and reliability for critical communications, safety, route planning, and entertainment. Intellian’s Flat Panel Series consists of a portfolio of Enterprise and Compact user terminals, based on active electronically scanned arrays (AESA) for Fixed Enterprise, Maritime and Land Mobility customers.

## Optimized Performance

Utilizing Intellian’s innovative antenna design, the OW11FV delivers the maximum throughput allowed on the OneWeb network. Offering the highest link margin, performance is guaranteed even over scan and at the lowest elevation angles, ensuring we meet the highest demands of land mobile customers.

## Customer Network Exchange

Intellian’s Customer Network Exchange (CNX) units are a critical component of any OneWeb user terminal installation, providing both the power and data connectivity to the Flat Panel user terminal, and the connectivity to customer equipment and networks. CNX variants are offered for specific deployment scenarios including Land Fixed, Maritime and Land Mobility.

## Seamless Connectivity

The OW11FV features Intellian’s advanced tracking technology, extended scan range, and blockage mitigation, improves connection reliability and availability even while in motion. Delivering the best performance at scan, the innovative flat panel



technology facilitates smooth reliable handovers, which ensure seamless and uninterrupted connectivity.

## Harsh Environment Performance

The OW11FV is designed to ensure dependable performance in even the most demanding environments, operating in extremely low temperatures down to -40 °C and up to +55 °C (-40 °F to 131 °F). Integrated radar rejection filtering ensures performance in high interference installations and reliable broadband services for customers situated in the most remote locations.

## Simplified Installation

The lightweight design and compact form factor of the OW11FV enables easy installation by a single person. The universal mount design supports a variety of vehicle mounts. Installation is further simplified through use of combined power and data over a single coax cable connecting the outdoor and in-vehicle units. The use of Intellian’s mobile app for site survey, automated configuration.

# Intellian “Enterprise” OW terminal

## Technical Specifications

Indoor Units	CNX-WIFI	CNX-RACK-AC	CNX-MOBILITY
<b>Dimensions</b>	21 cm x 17 cm x 8 cm (8.2" x 6.7" x 3.1")	44.2 cm x 25 cm x 4.4 cm (19" x 1 RU chassis)	30 cm x 20 cm x 4 cm (11.8" x 7.9" x 1.6")
<b>Weight</b>	0.6 kg (1.3 lb)	6.3 kg (13.9 lb)	1 kg (2.2 lb)
<b>Power</b>	18 W (max), 8 W (avg)	30 W (max), 16 W (avg)	18 W (max), 8 W (avg)
<b>Operating Temp</b>	0 °C to +40 °C (32 °F to 104 °F)	-25 °C to +55 °C (-13 °F to 131 °F)	-25 °C to +55 °C (-13 °F to 131 °F)
<b>Data Interface</b>	WiFi-6 4-port GigE RJ45	8-port GigE RJ45, 1x USB (Type-A) 1x NMEA0183 / 1x NMEA2000	4-port GigE RJ45 1x NMEA 0183 / 1x NMEA2000
<b>Power Input</b>	Universal AC Power (100 – 240VAC)	Dual 450 W Power Modules 100 – 240 VAC	External Power Supply Adapter (AC and DC variants available)

### Outdoor Unit

<b>Throughput (peak)</b>	DL: 195 Mbps / UL: 32 Mbps
<b>G/T</b>	10.7 dB/K
<b>EIRP</b>	+36.6 dBW (Dual Carrier)
<b>Field of View</b>	+/- 70° from Zenith, 360° Azimuth
<b>Size</b>	96 cm x 50 cm x 12 cm (37.8" x 19.7" x 4.7")
<b>Weight</b>	16 kg (35 lb)
<b>Power</b>	340 W (max) 300 W (avg)
<b>Ingress</b>	IP66
<b>Operating Temp</b>	-40 °C to +55 °C (-40 °F to 131 °F)
<b>Interface</b>	F-Type conn

### System Diagram

